

CEILING ACCESS HATCHES

Model KSTC/CAD (Concealed Grid)

For Use in Square or Beveled Edge Ceiling Tile

DATE



SPECIFICATIONS

GENERAL SCOPE:

Access doors shall be Karp Type KSTC/CAD as manufactured by Karp Associates, Inc., Maspeth, N.Y. Sizes shall be as indicated on the drawings.

CONSTRUCTION:

1. Frame shall be 20 gage hot dipped galvanized steel with a rib containing a flame retardant polyurethane gasket.
2. Door shall be 20 gage electro-galvanized mild steel.
3. Escutcheon caps shall be plastic molded with hinged flaps.
4. Locks shall be budget locks operated with square shanked key.

STANDARD SIZES (Special Sizes On Request)

| DOOR SIZE (IN.) | | SHIP WT. (LBS.) |
|-----------------|----|-----------------|
| X | Y | |
| 24 | 24 | 19.0 |
| 24 | 48 | 35.0 |

| PROJECT DATA | | | | | |
|-----------------------|---|---|----------------|--------|---------|
| Project Name: | | | | | |
| Architect: | | | | | |
| Contractor: | | | | | |
| Agent/Customer Name: | | | | | |
| Tagging Instructions: | | | | | |
| Special Instructions: | | | | | |
| PROJECT SCHEDULE | | | | | |
| Qty. | H | W | No. of Latches | Finish | Remarks |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |

