

SURFACE MOUNTED FLUSH ACCESS DOOR

Model DSB-214SM

For All Types of Construction

266 Broadway, Suite 302 Brooklyn, NY 11211 P: 877-266-0096 F:877-266-2814





SPECIFICATIONS

GENERAL SCOPE:

Access doors shall be Karp Type DSB-214SM as manufactured by Karp Associates, Inc., Melville, N.Y. Sizes shall be as indicated on the drawings.

CONSTRUCTION:

- 1.(a) On door sizes of 12×12 and smaller, door and frame shall be 16 gage steel (or if specified, stainless steel).
- (b) On larger sizes, door and frame shall be 14 gage steel (or if specified, stainless steel).
- 2. Trim shall be one piece construction.
- 3. Hinge shall be exposed continuous piano hinge.
- 4. Latches shall be flush and screwdriver operated, or shall be key operated cylinder lock with automatic dust shutter.
- 5. Finish shall be prime coat of rust inhibitive electrostatic powder, baked white enamel.

STANDARD SIZES

FRAME MTG SIZE H X W (IN.)	NUMBER OF LATCHES	SHIP WT. (LBS.)
8 x 8	1	1.8
12 x 12	1	4.2
16 x 16	2	7.0
24 x 24	4	13.7

PROJECT DATA				
Project Name:				
Architect:				
Contractor:				
Agent/Customer Name:				
Tagging Instructions:				
Special Instructions:				

DATE

PROJECT SCHEDULE						
Qty.	Н	w	No. of Latches	Finish	Remarks	





